



CATEGORY II REAR BLADES

7, 8 & 9FT

MANUAL & HYDRAULIC

The CAMMOND all manual adjustment rear blades are the answer to low cost, medium horse-power, earth moving requirements. These blades are easily set for swing offset, tilt and angle. Change ditching or grading angles by just pulling a pin. The heavy duty design is rugged and reliable, assuring years of trouble free use.

- Tractor Horsepower** Up to 95 Horsepower
- Offset Tilt & Angle** Manual
- King Pin & Pedestal Tube** . 3" solid round
- Main Beam** 5"x 5" steel tubing
- Moldboard** 1/4"x 19" boxed frame
- Offset & Pivot Plate** 5/8" thick
- 3-Point Hitch** Category II, clevis hitch
- Parking Stand** Fold-a-way
- Blade Angle** Up to 50 deg. right or left
- Blade Tilt** 20 deg. up or down
- Blade Offset** Up to 40" right or left
- Cutting Edge** 1/2"x 6" reversible



MODEL#	DESCRIPTION	WEIGHT
RB75	7' MANUAL CAT II REAR BLADE	770#
RB85	8' MANUAL CAT II REAR BLADE	800#
RB95	9' MANUAL CAT II REAR BLADE	830#
RB75H	7' HYDRAULIC CAT II REAR BLADE	790#
RB85H	8'HYDRAULIC CAT II REAR BLADE	820#
RB95H	9' HYDRAULIC CAT II REAR BLADE	850#
OPTIONS		
C38	3"x8" HYDRAULIC TILT CYLINDER	35#
H0910	9'x10' HYDRAULIC HOSE KIT (TILT)	10#
C314	3'x14" HYDRAULIC ANGLE CYLINDER	40#
H078	7'x8' HYDRAULIC HOSE KIT (ANGLE)	10#

BUILT TO LAST

902 Arlington Center, PMB 225 • Ada, OK 74820
 Ph: 580-332-9300 • Toll-Free 1-800-843-8354
 Fax: 580-332-9524 • www.cammond.com

Specifications Subject To Change Without Notice